

IP CCTV / Professional NVRs / Uniview - Uniarch

UV-NVR-216S2-P16

Uniarch



Features

- Uniarch
- NVR for IP cameras
- 16 CH
- 160 Mbps bandwidth supported
- Maximum resolution 8 Megapixel
- Compression Ultra265/H.265/H.264
- Alarms
- Audio output
- VGA and HDMI 4K output
- 2 x USB 2.0
- 16 PoE ports IEEE802.3af/at
- Mouse
- Space for 2 HDD up to 10 TB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniarch
Inputs for IP cameras	LAN port up to 16 channels
IP compatible cameras	UNIVIEW, ONVIF
Bidirectional audio	1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	Ultra265 / H.265 / H.264
Display resolution	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
PoE	16 POE ports (IEEE 802.3at, IEEE 802.3af)
Alarms	4 Inputs /1 Relay
Total bandwidth	160 Mbps downstream / 96 Mbps upstream
Main Stream recording	4K / 6Mpx /5Mpx / 4Mpx / 3Mpx / 1080p / 960p / 720p / D1 / 2CIF / CIF
Decoding	1x4K @ 30fps / 2x4MPx @ 30fps / 3x3MPx @ 25fps / 4x1080p @ 30fps / 8x720P @ 30fps/ 16xD1
External Backup	USB / HDD USB memory
Internal memory	2 SATA HDD 3.5" of up to 10 TB (not included)
Communication	2 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Smartphone App & PC Software
Power	220V AC / 9W
Dimensions / Weight	53(AI) x 380(An) x 315 (D) mm / 2.4 Kg